



Specifications ML 1680	
Conveyor belt type	PVC (15mm cleats) Rubber (17mm cleats)
Conveyor belt width	800mm
Trough angle	45 degrees
Capacity	150 tonne/hour (potatoes, 50 m/min)
Motor	Drum motor 5,5 kW
Conveyor belt speed	23 - 92 m/min (variable)
Voltage	Voltage 380-420V / 50Hz / 3~ Voltage 440-480V / 60Hz / 3~ Voltage 220-240V / 60Hz / 3~ Voltage 200-220V / 60Hz / 3~ Voltage 190-210V / 50Hz / 3~ Voltage 580-620V / 60Hz / 3~
Total weight	5880
Drawbar load	1500
Optional	
X-Stream feed conveyor	
Coupling ML side for MC / TAT / HAT	
Scrapers on support rollers	
Swivel limiting by poles	
Worklamp LED	
Wireless remote control (additional)	
External power connection, switches with belt (3~/10A)	

		Benaming	
		Hallenvuller ML 80	
Alg. ruwheid 3,2	Lastoleranties ISO 13920 BF Alg. toleranties ISO 2768-mk Opp. ruwheid ISO 1302	Tech. omschr.	
		Maatschets	
Laatste wijziging:		Opp. beh.	Status
		Blank/ruw onbehandeld	approved
Am. proj.	Wijz. datum	Get.	Tek. nr.
	30/10/2018	RBA	A1 ML80
Startdatum		Schaal	Gewicht
23/05/2016		1:50	4